



SECURITY AND BEYOND

DATASHEET

ATHINA CCTV 36

LED street luminaire suitable for integration of indoor IP-cameras with a dimension of max. H 200mm x Ø 140mm.

Optional: on/off switch- and light management



ARTICLE Nr.:	200.236.01
Description	ATHINA 36
Light engine	OWLS LEDrofit 36
Light source	Cree XTE
<hr/>	
Watt	102
Lumen/Watt	102
Total luminous flux / lm (+/- 10%)	10,404
Light distribution	Individually adjustable
Dark Sky conformity	full cut-off
Voltage / Frequency	90-277 V / 50-60 Hz
System power consumption / Watt	65 to 112
Power factor	>90
<hr/>	
Dimensions / mm (excl. adaptor)	l=760 / b=340 / h=200
Weight / kg	12
Correlated color temperature / Kelvin	5,000
CRI value / Ra	>70
LED nos.	36
Ambient temperature	-45 °C to +55 °C
Ingress protection	IP66
Installation height (recommended)	6-8 m
<hr/>	
Enclosure / cover	die cast aluminum / plastic
Dielectric strength - LED array glass	IK08
Lifetime LED array / hours (L70)	100,000
Warranty / months	60
<hr/>	
IP camera	as per customer requirement
Warranty / months	to be advised

- subject to modification engineering -

